John Quaif
AI0112
Qualified RPII/PIPA
Tester for inflatables
and games.

INSPECTION REPORT



Paul Quaif
AI0113
Qualified RPII/PIPA
Tester for inflatables
and games.

Unit 28, Forest Business Park, Argall Avenue, London, E10 7FB

Email: paulquaif58@gmail.com

Website: www.pjentertainments.co.uk

Office: 0208 509 0150 Paul: 07966 375 570 John: 07966 375 571					
Company Name FUNDAY BY Telephone No 08780 Email OFFICE @	TERTAINMENT 113993 FUNDAY LTO.	(OM)	COLPIN LVEST TIPTUE	ECOS OQH	
Serial No: FDE 001/4 Name of Inspector: PAUL QUAIF Inflatable Type: GAME		Date of Inspection: 22 - 05 - 25 Expiry Date of Inspection: 21 - 05 - 25 Size (L x W x H) (m) 3.5 x 3.5 x 0.8			
	7 7 7		Manufacturer: NOT MOWN		
	19 4RE			NOT KNOWN	
Structure	Anchorage Condition of anchor points		Su	Blower itability	
Seams and webbing	and weathing			let and outlet mesh	
	ed pariets and steps min		1-0 64	ble and plug	
Walls and towers firm				ppeller	
Grounding N A		al Materials	Re	eturn flap	
Sharp angles			V PA	AT test	
riessure (mate: googe,		N	A BI	ower type/electric	
Entraphient		N	IA M	otor cover/casing	
Stability		lides	lnhouse tested (PAT)		
cital aleksama bola				ower size (Hp)	
Air loss Check toys/obstacles	Height of walls (15			lower tube length (m) 1 · 25	
	Height of walls (m			umber of blowers (this unit)	
Markings HAND WRITTEN Height of walls (m) Identification Run Out (m)			P	etrol blowers only (4hp)	
Art work (no significant peeling) N/A Clamber net/foam		/ladder	P	lay Area (L x W) (m) 9 SQ M	
Fall off height (m)	Slide sheet			Number of users and user height	
Open side fall off height (m)		Totally Enclosed Structure		Naximum user height (m)	
Step and ramp size (m)	Exits and marking			Maximum users at 1.0m	
Internal wall height (m)	Deflation of user a			Maximum users at 1.2m	
Stitching	Pressure or user a	rea		Maximum users at 1.5m	
Trough depth N/A				Naximum users at 1.8	
Fabric (fire retardant)	INSPECT	ION RESULTS		ustomise max user height	
Fabric (strength)		PASS		Maximum users at customised	
Thread (non-rotting)	FAIL		h	eight	
Illiand from Lawrench					
Notes/Risk Assessment:				Signature of tester	
			F	Paul Quaif	
			J	ohn Quaif	

Comments:

This unit must always be used with 2-inch thick, high-density crash mats on all entrances and exits at a minimum of 1.2m from the unit.

DO NOT operate in wind speeds in excess of 24mph/38kph.

This unit must always be supervised by a competent adult who is capable of exercising authority over the users.

I certify that the above equipment has been inspected to RPII standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report.

If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose.

All anchor points must be used to secure the unit to the ground at all times.