John Quaif
AI0112
Qualified RPII/PIPA
Tester for inflatables
and games.

INSPECTION REPORT



Paul Quaif AI0113 Qualified RPII/PIPA Tester for inflatables and games.

Unit 28, Forest Business Park, Argall Avenue, London, E10 7FB

Email: paulquaif58@gmail.com

Website: www.pjentertainments.co.uk

Office	: 0208 509 0150	Paul: 07966	375 570 J	ohn: 07966 3	375 571		
Company Name FUNDA Telephone No 087 Email OFFICE	y biviert co II. (a) Funda	AINMENT 3993 4 LTD - COM	Address	WEST	NE COS DQH		
Serial No: FDE 2019 CO 2 Name of Inspector: PAUL QUAIF			Date of Inspection: 22 - 05 - 24 Expiry Date of Inspection: 21 - 05 - 25				
Inflatable Type: GANE			Size (L x W x H) (m) 5.2 × 6.8 × 3.1				
Theme GLADIATON DUEL BE		BED DNLY		ufacturer:	SUST INFLATABLES		
Place of Inspection	NR294	RE	Date of	Manufactur	e NOT KNOWN		
	<u></u>	A b			Blower		
Structure		Anchorage Condition of anchor points			Suitability		
Seams and webbing				DRINE	Inlet and outlet mesh		
Bed panels and steps firm Walls and towers firm		Type of anchor point ₽ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		2 2	Cable and plug	1	
Grounding APPLIED 85 KG		nor accessories			Impeller	~	
Sharp angles	THE CIEY STAGE		Materials		Return flap	-	
Pressure (water gauge) 4.2	Zips				PAT test	_	
Entrapment	Rop			NA	Blower type/electric	V	
Stability		Windows/netting		NA	Motor cover/casing	~	
Deflation / evacuation time			es	1	Inhouse tested (PAT)	-	
Air loss	Slide	platform height	t (m)		Blower size (Hp) 2	нΡ	
1111 1000		ht of walls (134 or			Blower tube length (m) 1 · 2	5	
Markings LAGEL		ht of walls (m)	X		Number of blowers (this unit)		
Identification LASEL	Run	Out (m)			Petrol blowers only (4hp)	_	
Art work (no significant peeling) Clamber ne		nber net/foam/la	adde		Play Area (L x W) (m)		
Fall off height (m)	Slid	e sheet			Number of users and user heig	ht	
Open side fall off height (m)	56	Totally Enclos	ed Structure	9	Maximum user height (m)	-	
Step and ramp size (m)		Exits and markings			Maximum users at 1.0m	2	
Internal wall height (m)	1.0	ation of user are			Maximum users at 1.2m	2	
Stitching	Pres	sure or user afe	a		Maximum users at 1.5m	2	
Trough depth 20/63cm					Maximum users at 1.8	2	
Fabric (fire retardant)		INSPECTION RESULTS			Customise max user height		
Fabric (strength)		PASS			Maximum users at customised	_	
Thread (non-rotting)		FAIL			height		

Notes/Risk Assessment:	Signature of tester		
,	Paul Quaif		
*.	John Quaif		

Comments:

This unit must always be used with 2-inch thick, high-density crash mats on all entrances and exits at a minimum of 1.2m from the unit.

DO NOT operate in wind speeds in excess of 24mph/38kph.

This unit must always be supervised by a competent adult who is capable of exercising authority over the users.

I certify that the above equipment has been inspected to RPII standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report.

If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose.

All anchor points must be used to secure the unit to the ground at all times.